



Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1200 lm/ft	9.7 W/ft	124 lm/W	SO
1200 lm/ft	9.8 W/ft	122 lm/W	BW
1000 lm/ft	9.4 W/ft	144 lm/W	GZ
1000 lm/ft	9.8 W/ft	109 lm/W	NW
1000 lm/ft	9.5W/ft	111 lm/W	WW
1000 lm/ft	9.5W/ft	111 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver

Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Ordering Guide

TB4DLED									
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING	
TB4DLED	BEAM 4 - Pendant Direct LED	400	400 lm/ft - Minimum	80	80 CRI	30	3000 K	SO	spotless lens
		1000	1000 lm/ft - max for GZ, NW, WW, ASO.*			35	3500 K	ASO	Asymmetric
						40	4000 K	BW	Batwing
		1200	1200 lm/ft - Maximum					NW	Narrow
								GZ	Graze
								WW	Wallwash
		Outputs between listed min and max are available. * 1000 lm/ft max. only for GZ, NW, WW and ASO.						*Lens options use spotless lens. Choose only one of the options above.	
								Available in 1" increments.	
								* Additional 5 working days required.	

VOLTAGE	DRIVER	CIRCUITS	MOUNTING	BATTERY (OPTIONAL)
120 120 V	DP dimming (0-10V) 1%	1 1 circuit	CA(#) drywall+cable length (36" std.)	B(#) battery pack (integral)
277 277 V		2 2 circuits	CT9(#) TB/TG 9/16+cable length (36" std.)	
347 347 V		+E(#) emergency circuit*	CT15(#) TB/TG15/16+cable length (36" std.)	
UNV universal			CTS(#) screw slot+cable length (36" std.)	
			SA(#) drywall+stem length >48" (18" std.)	
			CASL(#) drywall cable sloped ceiling	
			SASL(#) drywall stem sloped ceiling	
		*Specify quantity	See Mounting kit guide for full specification code. White canopy standard	Minimum 5ft; Not available with 347V Please consult factory

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.