



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
1200 lm/ft	9.4 W/ft	128 lm/W	FL



**cULus Listed
Type I.C.**

Ordering Guide

B6RLED															
PRODUCT ID		NOM. LUMENS/FT		CRI		COLOR TEMP.		SHIELDING		LENGTH		FINISH		VOLTAGE	
B6RLED	Beam 6	400	400 lm/ft - Min	80	80 CRI	30	3000 K	FL	flush spotless lens	4	4'	W	white	120	120 V
	Recessed LED	1200	1200 lm/ft - Max			35	3500 K	ASO	asymmetric with SO lens	5	5'	BLK	black*	277	277 V
						40	4000 K			6	6'	AP	aluminum paint*	347	347 V
										8	8'			UNV	universal
										12	12'				
								S(L) system run							
		Outputs between listed min and max are available.								Available in 1' increments.		*Additional 5 working days required.			

DRIVER		CIRCUITS		MOUNTING		BATTERY (OPT.)		OTHER (OPT.)		QS	QUICKSHIP +
DP	dimming (0-10V) 1%	1	1 circuit	TB9	t-bar 9/16"	B(#)	battery pack	EF	end feed		
		2	2 circuits	TB15	t-bar 15/16"		4' sections	FW	flex whip (6' std)*		
		+E(#)	emergency circuit*	ST	screw slot t-bar			CP	Chicago plenum		
				TG9	tegular 9/16"			HD	hold down clip**		
				TG15	tegular 15/16"						
				DF	drywall flange						
				D	drywall flangeless						
				DB	slip-through bracket						
				DS	drywall spackle flange						
		*Specify quantity				Not available with 347V. Please consult factory		* Other lengths available; please consult factory. ** Only available for t-bar mounting			

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.