

Stand Alone Decoratives


Chime Cylinder

PENDANT



Black with Silver Chrome trim Wood with Silver Chrome trim Black with Black trim White with White trim White with Silver Chrome trim

SIDE VIEWS (ALL AVAILABLE SIZES)



Project _____

Type _____

Notes _____

PERFORMANCE PER FIXTURE

BEAM ANGLE	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
NB	1765 lm	20 W	88 lm/W
MB	1824 lm	20 W	91 lm/W
WB	1653 lm	20 W	83 lm/W



Ordering Guide

CCPD						90										
PRODUCT ID		LENGTH		BEAM ANGLE		NOM. LUMENS		CRI		COLOR TEMP.		HOUSING FINISH		VOLTAGE		
CCPD	Chime Cylinder	1.5	1.5'	NB	narrow	HI	high lumen output	90	90 CRI	27	2700K	NMP	maple wood with natural finish		UNV	universal (120-277V)
	Pendant	2	2'	MB	medium*					30	3000K	BLK	metal with black finish			
		3	3'	WB	wide					35	3500K	W	metal with white finish			
					40					4000K						
				* Default option.												

DRIVER	TRIM FINISH	MOUNTING	MOUNTING FINISH	PENDANT CABLE LENGTH
DP dimming (0-10V or TRIAC) 1% *	SCR silver chrome BLK black* W white**	FCP flat stand alone canopy, driver in j-box	BLK black W white	TLA(L) cable length adjustable (specify length between 6" and 140" – includes 18" of additional internal cable for on-site adjustment)
* TRIAC dimming for line voltage capable (120V voltage only), purple and pink wires need to be capped in that case.	* Not available with NMP (natural maple) and W (white) housing. ** Not available with NMP (natural maple) and BLK (black) housing.	Round canopy used.		Black, plenum rated cable, 1/8" diameter used.

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.

Patent number: 11,118,765

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

|||
June 15, 2023

FILE NAME:CCPD_QS.SPEC

© 2016 Axis Lighting Inc.
1.800.263.2947
[T] 514.948.6272

axis
axislighting.com