

# Stand Alone Decoratives

## Chime Taper

PENDANT



Project \_\_\_\_\_


Type \_\_\_\_\_

Notes \_\_\_\_\_

### PERFORMANCE PER FIXTURE

BEAM ANGLE	NOMINAL LUMEN OUTPUT	INPUT WATTS	EFFICACY
NB	1765 lm	20 W	88 lm/W
MB	1824 lm	20 W	91 lm/W
WB	1653 lm	20 W	83 lm/W

### SIDE VIEWS (ALL AVAILABLE SIZES)



## Ordering Guide

CTPD				90		NMP	
PRODUCT ID	LENGTH	BEAM ANGLE	NOM. LUMENS	CRI	COLOR TEMP.	HOUSING FINISH	VOLTAGE
CTPD Chime Taper Pendant	1.5 1.5' 2 2' 3 3'	NB narrow MB medium* WB wide	HI high lumen output	90 90 CRI	27 2700K 30 3000K 35 3500K 40 4000K	NMP natural maple	UNV universal (120-277V)
		* Default option.					

DRIVER	TRIM FINISH	MOUNTING	MOUNTING FINISH	PENDANT CABLE LENGTH
DP dimming (0-10V or TRIAC) 1%	SCR silver chrome	FCP flat stand alone canopy, driver in j-box*	BLK black W white	TLA(L) cable length adjustable (specify length between 6" and 140" – includes 18" of additional internal cable for on-site adjustment)
* Triac dimming for line voltage capable (120V voltage only), purple and pink wires need to be capped in that case.		Round canopy used.		Black, plenum rated cable, 1/8" diameter used.

**Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.**

**Patent number: 11,118,765**

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

1 / 3  
June 15, 2023

FILE NAME:CTPD\_QS.SPEC

© 2016 Axis Lighting Inc.  
1.800.263.2947  
[T] 514.948.6272

