



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project

Type

Notes

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI			
NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
500 lm/ft	5.6 W/ft*	90 lm/W	FL
500 lm/ft	9.5 W/ft*	51 lm/W	RG
1000 lm/ft	10.2 W/ft*	97 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver



Ordering Guide

SCD									
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING	
SCD	Sculpt Pendant Direct	300	300 lm/ft - Min	80	80 CRI	30	3000 K	FL	flush
		1000	1000 lm/ft - Max			35	3500 K	RG	0.5" regressed
						40	4000 K	ASO	Asymmetric

VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)	
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B(#)	battery pack
277	277 V			2	2 circuits	CT9(#)	TB/TG 9/16+cable length (36" std.)		
347	347 V			+E(#)	emergency circuit*	CT15(#)	TB/TG15/16+cable length (36" std.)		
UNV	universal					CTS(#)	screw slot+cable length (36" std.)		
						CASL(#)	drywall cable sloped ceiling		
						+SM	seismic kit		
				*Specify quantity		See Mounting kit guide for full specification code. Specify length.		Minimum 5ft; Not available with 347V Please consult factory	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.