



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project

Type

Notes

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT		INPUT WATTS*	EFFICACY	SHIELDING I/D
UPLIGHT	DOWNLIGHT			
750 lm/ft	500 lm/ft	11.9 W/ft	105 lm/W	SO/FL
	500 lm/ft	9.5 W/ft	51 lm/W	RG
	1000 lm/ft	10.2 W/ft	97 lm/W	ASO

Please consult factory for custom lumen output and wattage.

DLC Approved Options

OUTPUT UP	OUTPUT DOWN	CRI	CCT	SHIELDING	LENGTH	VOLTAGE
300 lm/ft	300 lm/ft	80	3000 K	FL	4'-12'	UNV
500 lm/ft	400 lm/ft		3500 K			
750 lm/ft	500 lm/ft		4000 K			



Ordering Guide

SCWDI													
PRODUCT ID		NOM. LUM/FT UP		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING INDIRECT		SHIELDING DIRECT	
SCWDI	Sculpt Wall	300	300 lm/ft - Min	300	300 lm/ft - Min	80	80 CRI	30	3000 K	SO	spotless lens	FL	flush
	Direct/Indirect	1000	1000 lm/ft - Max	500	500 lm/ft - Max			35	3500 K			RG	0.5" regressed
								40	4000 K			ASO	Asymmetric
		Outputs between listed min and max are available.											

LINEAR LENGTH (FT)		FINISH		VOLTAGE		DRIVER		CIRCUITS		BATTERY (OPTIONAL)	
#	4 ft - 12 ft continuous length	W	white	120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	B(#)	battery pack
S(L)	System Run	BLK	black*	277	277 V			2	2 circuits		
		AP	aluminum paint*	347	347 V			+E(#)	emergency circuit*		
				UNV	universal						
Available in 1' increments.		* Additional 5 working days required.						*Specify quantity		5' minimum. For lengths under 5' battery pack is remote only. Not available with 347V. Please consult factory	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.