



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
500 lm/ft	5.6 W/ft*	90 lm/W	FL
500 lm/ft	9.5 W/ft*	51 lm/W	RG
1000 lm/ft	10.2 W/ft*	97 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver



Ordering Guide

SCS																
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING		LINEAR LENGTH (FT)		FINISH				
SCS	Sculpt Surface	300	300 lm/ft - Min	80	80 CRI	30	3000 K	FL	flush	#	4 ft - 12 ft continuous length	W	white			
		1000	1000 lm/ft - Max			35	3500 K	RG	0.5" regressed				S(L)	System Run	BLK	black*
						40	4000 K	ASO	Asymmetric						AP	aluminum paint*

VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)	
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	SB9	surface TB/TG 9/16	B(#)	battery pack 4' sections
277	277 V			2	2 circuits	SB15	surface TB/TG 15/16		
347	347 V			+E(#)	emergency circuit*	SBS	surface screw slot t-bar		
UNV	universal					S	surface drywall ceiling		
				*Specify quantity				Not available with 347V Please consult factory	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.