



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project _____

Type _____

Notes _____

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI

NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
500 lm/ft	5.6 W/ft*	90 lm/W	FL
500 lm/ft	9.5 W/ft*	51 lm/W	RG
1000 lm/ft	10.2 W/ft*	97 lm/W	ASO

* Based on a 4 foot flush luminaire using one driver



Ordering Guide

SCWD													
PRODUCT ID		NOM. LUM/FT DOWN		CRI		COLOR TEMP.		SHIELDING		LINEAR LENGTH (FT)		FINISH	
SCWD	Sculpt Wall Direct	300	300 lm/ft - Min	80	80 CRI	30	3000 K	FL	flush	#	4 ft - 12 ft continuous length	W	white
		1000	1000 lm/ft - Max			35	3500 K	RG	0.5" regressed	S(L)	System Run	BLK	black*
						40	4000 K	ASO	Asymmetric			AP	aluminum paint*
		Outputs between listed min and max are available.						Lens options use spotless lens		Available in 1" increments.		* Additional 5 working days required.	

VOLTAGE		DRIVER		CIRCUITS		BATTERY (OPT.)	
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	B(#)	battery pack 4' sections
277	277 V			2	2 circuits		
347	347 V			+E(#)	emergency circuit*		
UNV	universal						
				*Specify quantity		Not available with 347V Please consult factory	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.