



Refer to axislighting.com for complete fixture details, IES files, and installation instructions

Project

Type

Notes

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI			
NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
750 lm/ft	6.4 W/ft	118 lm/W	SO
750 lm/ft	7.3 W/ft	103 lm/W	BW

Please consult factory for custom lumen output and wattage.



Ordering Guide

SCI											
PRODUCT ID		NOM. LUM/FT UP		CRI		COLOR TEMP.		SHIELDING		LINEAR LENGTH (FT)	
SCI	Sculpt Pendant Indirect	300	300 lm/ft - Minimum	80	80 CRI	30	3000 K	SO	spotless lens	#	4 ft - 12 ft continuous length
		1000	1000 lm/ft - Maximum			35	3500 K	BW	batwing lens	S(L)	System Run
						40	4000 K				
		Outputs between listed min and max are available.						Available in 1' increments.			
										* Additional 5 working days required.	

VOLTAGE		DRIVER		CIRCUITS		MOUNTING		BATTERY (OPTIONAL)				
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	CA(#)	drywall+cable length (36" std.)	B(#)	battery pack 4' sections			
277	277 V			2	2 circuits	CT9(#)	TB/TG 9/16+cable length (36" std.)					
347	347 V			+E(#)	emergency circuit*	CT15(#)	TB/TG15/16+cable length (36" std.)					
UNV	universal					CTS(#)	screw slot+cable length (36" std.)					
						CASL(#)	drywall cable sloped ceiling					
						+SM	seismic kit					
				*Specify quantity		See Mounting kit guide for full specification code. Specify length		Not available with 347V Please consult factory				

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.