



Refer to [axislighting.com](http://axislighting.com) for complete fixture details, IES files, and installation instructions

Project

Type

Notes

PERFORMANCE PER LINEAR FOOT AT 3500K, 80 CRI			
NOMINAL LUMEN OUTPUT	INPUT WATTS*	EFFICACY	SHIELDING
750 lm/ft	6.4 W/ft	118 lm/W	SO

Please consult factory for custom lumen output and wattage.



Ordering Guide

SCWI													
PRODUCT ID		NOM. LUM/FT UP		CRI		COLOR TEMP.		SHIELDING INDIRECT		LINEAR LENGTH (FT)		FINISH	
SCWI	Sculpt Wall Indirect	300	300 lm/ft - Minimum	80	80 CRI	30	3000 K	SO	spotless lens	#	4 ft - 12 ft continuous length	W	white
		1000	1000 lm/ft - Maximum			35	3500 K			S(L)	System Run	BLK	black*
						40	4000 K					AP	aluminum paint*
		Outputs between listed min and max are available.						Blank extrusion on direct		Available in 1' increments.		* Additional 5 working days required.	

VOLTAGE		DRIVER		CIRCUITS		BATTERY (OPT.)	
120	120 V	DP	dimming (0-10V) 1%	1	1 circuit	B(#)	battery pack
277	277 V			2	2 circuits		
347	347 V			+E(#) emergency circuit*			
UNV	universal						
				*Specify quantity		4' minimum. For lengths under 4' battery pack is remote only. Not available with 347V Please consult factory	

Refer to specification sheets for complete details. Note that only options shown above qualify for QuickShip+.