








Project _____
Type _____
Notes _____



8x16 ft Bow tie shape:
1 x Framework: 4ft segments (8) + LC90 Hub (8)
8 x Direct AxisTrak™ Inserts (4ft)



9x19 ft Bow tie shape:
1 x Framework: 5ft segments (8) + LC90 Hub (8)
8 x Direct AxisTrak™ Inserts (5ft)
8 x Indirect Surroundlite Inserts (5ft)



10x22 ft Bow tie shape:
1 x Framework: 6ft segments (8) + LC90 Hub (8)
8 x Direct AxisTrak™ Inserts (6ft)
8 x Indirect Surroundlite Inserts (6ft)



Project _____

Type _____

Notes _____

AxisTrak™ decoratives must be ordered separately. Please follow the link:



Ordering Guide Framework

PRODUCT ID	FINISH	UNV VOLTAGE	CONTROLS	CIRCUITS	MOUNTING/SUSPENSION	CANOPY
8x16ft Bow tie shape Pendant 9x19ft Bow tie shape Pendant 10x22ft Bow tie shape Pendant	BLK black W white AP aluminum paint C(#) custom	UNV universal	IMW Integral Modular Wiring for 0-10V dimming (1%) with DP integral driver IMWD Integral Modular Wiring for DALI 2.0 with DALIT6 integral driver	Number of circuits will depend on the ordered kit, and matches lighting Zone count	CA(#) drywall+cable length (36" std.)* SLV(#) drywall+stem length <48" (18" std.) leveling	RC round canopy SC square canopy
					Specify suspension length * See Mounting kit guide for full specification code. White canopy standard. Other canopies are available. Please visit the link above.	Not available with (SLV) stem mounting.

Ordering Guide Linear Lighting Inserts

SFLDAXT PRODUCT ID	TOTAL LENGTH	UNV VOLTAGE	CONTROLS	HOUSING FINISH
SFLDAXT StencilFlex® AxisTrak™ Insert	4 4' 5 5' 6 6'	UNV universal	DPCV integral 48V driver 60W max. 0-10V dimming through two added contacts on AxisTrak™ DALIT6CV integral 48V driver 60W max. DALI dimming through two added contacts on AxisTrak™	BLK black W white
		Wired for 120V to determine power drops.		! Please be mindful of your Framework Color Selection when selecting your insert housing finish.

PRODUCT ID	TOTAL LENGTH	TOTAL LUMENS/FT	CRI	COLOR TEMP.	VOLTAGE	CONTROLS
SFLISL StencilFlex® Indirect SurroundLite Insert	5 5'* 6 6'	175 175 lm/ft 250 250 lm/ft 350 350 lm/ft 500 500 lm/ft 700 700 lm/ft 1000 1000 lm/ft	80 80 CRI 90 90 CRI	27 2700 K 30 3000 K 35 3500 K 40 4000 K	UNV universal	DP integral driver 0-10V dimming (1%) - wired DALIT6 integral driver DALI 2.0 Type 6 - wired
	*2 feet lit segment.					

Patented Design

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.