





Project _____


Type _____

Notes _____




4ft Square:

- 1 x Framework: 4ft segments (4) + L90Hub (4)
- 2 x Direct Flush Spotless Lens Inserts (4ft)
- 1 x Optional Softzone 90° Triangle TR90 panel (4ft)



5ft Square:

- 1 x Framework: 5ft segments (4) + L90Hub (4)
- 2 x Direct Flush Spotless Lens Inserts (5ft)
- 2 x Indirect Surroundlite Inserts (5ft)
- 1 x Optional Softzone 90° Triangle TR90 panel (4ft)



6ft Square:

- 1 x Framework: 6ft segments (4) + L90Hub (4)
- 2 x Direct Flush Spotless Lens Inserts (6ft)
- 2 x Indirect Surroundlite Inserts (6ft)
- 1 x Optional Softzone 90° Triangle TR90 panel (4ft)



4x8 ft Rectangle:

- 1 x Framework: 4ft segments (6) + L90Hub (4) + I180 (2)
- 2 x Direct Flush Spotless Lens Inserts (4ft)
- 2 x Optional Softzone 90° Triangle TR90 panel (4ft)



5x10 ft Rectangle:

- 1 x Framework: 5ft segments (6) + L90Hub (4) + I180 (2)
- 2 x Direct Flush Spotless Lens Inserts (5ft)
- 2 x Indirect Surroundlite Inserts (5ft)
- 2 x Optional Softzone 90° Triangle TR90 panel (4ft)



6x12 ft Rectangle:

- 1 x Framework: 6ft segments (6) + L90Hub (4) + I180(2)
- 2 x Direct Flush Spotless Lens Inserts (6ft)
- 2 x Indirect Surroundlite Inserts (6ft)
- 2 x Optional Softzone 90° Triangle TR90 panel (4ft)

Patented Design

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.

Project _____

Type _____

Notes _____

Ordering Guide Framework

PRODUCT ID	FINISH	UNV VOLTAGE	CONTROLS	CIRCUITS	MOUNTING/SUSPENSION	CANOPY
4 foot Square Pendant 5 foot Square Pendant 6 foot Square Pendant 4x8 foot Rectangle Pendant 5x10 foot Rectangle Pendant 6x12 foot Rectangle Pendant	BLK black W white AP aluminum paint C(#) custom*	UNV universal	IMW Integral Modular Wiring for 0-10V dimming (1%) with DP integral driver IMWD Integral Modular Wiring for DALI 2.0 with DALIDT6 integral driver	Number of circuits will depend on the ordered kit, and matches lighting Zone count	CA(#) drywall+cable length (36" std.) SLV(#) drywall+stem length <48" (18" std.) leveling	RC round canopy SC square canopy
* You can match framework finish to Standard Palette Softzone panels.					Specify suspension length * See Mounting kit guide for full specification code. White canopy standard. Other canopies are available. Please visit the link above.	Not available with (SLV) stem mounting.

Ordering Guide Linear Lighting Inserts

SFLDSOFL					UNV	
PRODUCT ID	MODULE LENGTH	TOTAL LUMENS/FT		CRI	COLOR TEMP.	VOLTAGE
SFLDSOFL StencilFlex® Direct Linear Insert SO Flush Lens	4 4'	200	200 lm/ft	80 80 CRI	27 2700 K	UNV universal Wired for 120V to determine power drops.
	5 5'	300	300 lm/ft	90 90 CRI	30 3000 K	
	6 6'	400	400 lm/ft		35 3500 K	
					40 4000 K	

PRODUCT ID		TOTAL LENGTH	TOTAL LUMENS/FT	CRI	COLOR TEMP.	VOLTAGE	CONTROLS	
SFLISL	StencilFlex® Indirect SurroundLite Insert	5 5"	175 175 lm/ft	80 80 CRI	27 2700 K	UNV universal	DP	integral driver 0-10V dimming (1%) - wired
		6 6'	250 250 lm/ft	90 90 CRI	30 3000 K		DALIDT6	integral driver DALI 2.0 Type 6 - wired
			350 350 lm/ft		35 3500 K			
			500 500 lm/ft		40 4000 K			
			700 700 lm/ft					
			1000 1000 lm/ft					
		*2 feet lit segment.						

Ordering Guide SoftZone® Panels (Optional)

PRODUCT ID		()											
		Panel ID (Color)											
		PANEL ID		SOFTZONE PANEL COLOR									
SFSZ	StencilFlex® Softzone Panels	Triangle	TR904	4' triangle- 90° only	COT	cotton		SAN	sand		PUR	purple	
					CUSMAR	marble		COR	cork		OCE	ocean	
					TIN	tin		LEM	lemon		CUSNAV	navy	
					CON	concrete		CUSAPP	apple green		CUSPEB	pebble	
					SLA	slate		BRI	brick		CUSSHA	shadow	
					CAR	carbon		CUSMAN	maroon				
					Matching framework finishes available.								

Patented Design

Product design and development is an ongoing process at Axis Lighting. We reserve the right to change specifications. Contact Axis for the latest product information.