SkyeFall

eaturing a planar recessed 2'x2' footprint that delivers a clean esthetic whether on its own or in combination with different lens depths to form stunning luminous ceilings. Indeed, SkyeFall presents a choice of droplens heights, from flush to 7", for a fresh, new approach to playing with illuminated volumes. On top of adding interest to the ceiling line, SkyeFall lets you add layers of luminance to adjacent ceilings and walls based on the selected drop-lens dimension.

SkyeFall is a quality product with crisp corners and a uniform glow, all in a recessed housing less than 5" deep. Flexible, luminous and playful – made to inspire.

| | | | | | | , | made to mspire. |
|------------|----------------|----------------------|------------|-------------------------|-----------------------------|--------------------|---|
| | | | | | | | |
| Size | Depth | Output | CRI | Color Temp. | Voltage | Flnish | Driver |
| 2'x2' | 4 5/16" | 2400-4000 lm | 80 90 | 3000K 3500K 4000K | 120V 277V 347V UNV | White | 0-10V - 1% Standard Lutron Bi-level dimming Other |
| onsult spe | ec sheet for e | exact output & speci | fications. | | | CONTROL SENSORS | Citas Listed Type I.C. |
| lush | | Tegular | | 1" | 2" | | 3" |
| = | | 5" | | 6" | 7" | | |
| | | | | | | 90° 75° 60° 45° | 90° 75° 60° 416 416 278 416 45° 30° |

Lumaire Lumens: 2902 lm Input Watts: 33 W Efficacy: 88 lm/W

CCT: 3500K

